



## ***ROOFTEK PREP #3154 CLEAR*** ***Technical Data & Application Instructions***

**SOLATEK ROOFTEK PREP #3154 CLEAR**  
**TECHNICAL DATA & APPLICATION INSTRUCTIONS**

### ***PRODUCT DESCRIPTION***

**ROOFTEK PREP #3154 CLEAR** is manufactured using modified acrylic, low viscosity elastomer of the highest quality resins without the addition of plasticizers. Production is rigidly controlled to assure uniformity of quality in every batch of materials. **ROOFTEK PREP #3154 CLEAR** is a water-based, elastomeric primer where premium quality acrylic resins are combined with reinforcing laminar pigments, an effective biocide package and non-migrating fire retardants, resulting in superior durability, weatherproofing, ultraviolet resistance and algae/mildew resistance. **ROOFTEK PREP #3154 CLEAR** is a high-tensile strength coating for use as a primer coat to improve the adhesion to prior deck systems or new deck substrates. It is designed as a bonding primer to enhance the adhesion of **SOLATEK** topcoats over previously coated surfaces or new construction. It also wets into existing substrates or existing coatings to lock down residual dust or contamination, thereby maximizing adhesion of the subsequent acrylic topcoat.

### ***APPLICATION***

Surfaces shall be clean and dry, and free of dirt, dust, loose granules, pollution fallout or other contamination. Thoroughly mix containers to achieve an even consistency prior to use. Apply **ROOFTEK PREP #3154 CLEAR** at the rate of approximately 200 sq. ft. per gallon to the properly prepared surface. Substrate porosity and texture will determine the amount of **ROOFTEK PREP #3154 CLEAR** to prime the surface. Allow **ROOFTEK PREP #3154 CLEAR** to dry thoroughly prior to top coating.

### ***PRECAUTIONS***

**ROOFTEK PREP #3154 CLEAR** will freeze and become unusable at temperatures below 32°F (0°C). Do not apply at temperatures below 60°F (7°C). Do not apply if weather conditions will not allow the **ROOFTEK PREP #3154 CLEAR** to dry before rain, dew or freezing temperatures. For additional information refer to the MSDS.



21595 Curtis Street • Hayward, CA 94545  
(510) 887-7254 • Fax: (510) 887-5637  
[www.solatekcoatings.com](http://www.solatekcoatings.com)



Our products are guaranteed to meet established quality control standards and product specification at the time of shipment. Information contained in our technical data is based on laboratory and field testing, but is subject to change without prior notice. No guarantees of accuracy are given or implied, nor does TRESKO assume any responsibility for coverage, performance or injuries resulting from storage, handling or use of our products. Neither seller nor manufacturer has any knowledge or control concerning the purchaser's use. The only obligation of either seller or manufacturer shall be to replace any quantity of this product, which is proved to be defective. Any claim of defective product must be received in writing within one year from date of shipment.